



THE PREMIER SOURCE FOR APPLICATION SPECIFIC MULTILAYER CAPACITORS

Products by Market	AEROSPACE & AVIONICS	AUTOMOTIVE	MEDICAL	MILITARY & DEFENSE	OIL EXPLORATION	POWER CONVERSION	TELE/DATACOM
COG -COMMERCIAL - 16Vdc to 10KVdc - 12		●	●	●		●	●
X7R- COMMERCIAL - 16Vdc to 10KVdc - 14		●	●	●		●	●
HIGH CAP VALUE MLC - X7R & X5R - 16			●	●		●	●
Z5U & Y5V DIELECTRIC - 18		●				●	●
BX DIELECTRIC - 19	●	●		●			
HIGH RELIABILITY TESTING -20	●		●	●	●	●	
MIL-PRF SCREENING FLOWCHARTS - 21	●		●	●		●	
COG - HIGH RELIABILITY-16Vdc to 10KVdc - 22	●		●	●		●	
X7R - HIGH RELIABILITY-16Vdc to 10KVdc - 24	●		●	●		●	
FLEXICAP® POLYMER TERMINATION - 26	●	●	●	●		●	●
200°C HIGH TEMPERATURE - COG - 28	●	●		●	●		
200°C HIGH TEMPERATURE - CLASS II - 29	●	●		●	●		
LEADED HIGH TEMP.- ENCAPSULATED - 30	●	●		●	●		
HIGH TEMPERATURE EPOXY COATED - 31	●	●		●	●		
X8R HIGH TEMPERTURE - 150°C - 33		●		●			
PULSED POWER CAPACITORS - 34			●	●	●		
DETONATOR & PULSE ENERGY - 36				●	●		
Y3 CERTIFIED SAFETY - 38							●
Y2 CERTIFIED SAFETY - 39							●
TIP & RING CAPACITORS - 40							●
THIN PROFILE CAPACITORS - 41		●	●	●			●
CAPACITOR ARRAYS - 42	●	●	●	●		●	●
AXIAL LEADED - COMMERCIAL 44		●	●	●		●	●
RADIAL LEADED - COMMERCIAL - 46		●	●	●		●	●
RADIAL LEAD H.V.- COMMERCIAL - 48		●	●	●		●	●
RADIAL LEAD H.V.-HIGH RELIABILITY - 50	●		●	●		●	●
DSCC APPROVED - RADIAL LEAD HV - 52	●			●		●	
DSCC 87106 - CAPACITOR ASSEMBLIES - 53	●			●		●	
ST & SM - CAPACITOR ASSEMBLIES - 54	●		●	●		●	●
APPLICATION SPECIFIC - 56	●	●	●	●	●	●	●

TABLE OF CONTENTS

INTRODUCTION	4
APPLICATION NOTES	6
DIELECTRIC CHARACTERISTICS	8
SMT CHIP PART NUMBER BREAKDOWN	10
CODES AND DIMENSIONS	11
COG - COMMERCIAL - 16Vdc to 10KVdc	12
X7R - COMMERCIAL - 16Vdc to 10KVdc	14
HIGH CAPACITANCE VALUE MLC - X7R & X5R	16
Z5U & Y5V DIELECTRICS	18
BX DIELECTRICS	19
HIGH RELIABILITY TESTING	20
MIL-PRF SCREENING FLOWCHARTS	21
COG - HIGH RELIABILITY - 16Vdc to 10KVdc	22
X7R - HIGH RELIABILITY - 16Vdc to 10KVdc	24
FLEXICAP® POLYMER TERMINATION	26
200°C HIGH TEMPERATURE - COG	28
200°C HIGH TEMPERATURE - CLASS II	29
LEADED HIGH TEMP. ENCAPSULATED	30
LEADED HIGH TEMPERATURE EPOXY COATED	31
200°C - DIELECTRIC CHARACTERISTICS	32
X8R - HIGH TEMPERATURE 150°C	33
PULSE POWER CAPACITORS	34
DETONATOR & PULSE ENERGY	36
Y3 - CERTIFIED SAFETY CAPACITORS	38
Y2 - CERTIFIED SAFETY CAPACITORS	39
TIP & RING CAPACITORS	40
THIN PROFILE CAPACITORS	41
CAPACITOR ARRAYS	42
AXIAL LEADED - COMMERCIAL	44
RADIAL LEADED - COMMERCIAL	46
RADIAL LEADED HV - COMMERCIAL	48
RADIAL LEADED HV - HIGH RELIABILITY	50
DSCC APPROVED - RADIAL LEADED	52
DSCC 87106 - CAPACITOR ASSEMBLIES	53
ST AND SM - CAPACITOR ASSEMBLIES	54
APPLICATION SPECIFIC	56
CHIP MARKING SYSTEM	58
TAPE & REEL SYSTEM	59

